



UGFI20AD-GRN

By Killark
Catalog # [UGFI20AD-GRN](#)

20A, 125VAC Portable GFCI Receptacle With Green LED.



Features

- No need to permanently alter existing installations
- Portable Unit can be temporarily hung using included strap near an existing receptacle wherever protection is required.
- Factory Sealed Unit.
- Acceptor® plug and cord set included with Adapter Unit. Cord is 36".
- GFCI device also provides circuit protection, for connected apparatus, against current overload and short circuits.
- Acceptor® receptacles and plugs are intermateable with both Crouse-Hinds® ArkGard®2 and Appleton® U-Line® products.
- Amber pilot light provides indication that the receptacle is energized.
- Units can be Padlocked OFF for maintained safety.
- Fully gasketed GFCI compartment prevents moisture from damaging electronic components.
- Same high quality materials as the standard ACCEPTOR®.

General

Series UGFI
UPC 783936660899

Dimensions

Weight 16 lb

Electrical Ratings

Amperage Rating 20
Voltage Rating 125 VAC

Certifications and Compliance

CSA File Number LR14667
Hazardous Rating(s)

- Class 1, Division 2, Groups B, C, D
- Class I, Zone 2, Groups IIB+H2, IIA
- Class II, Divisions 1 & 2, Groups F, G
- Class III, Divisions 1 & 2

UL File Number E91049

Product Assets

[Installation Manuals - UGFI 1P Series Factory Sealed Portable GFCI Receptable IOM K1181](#)



A proud member of the Hubbell Family.